Document ID: EDF-ER-315

Revision ID:

Effective Date: 05/14/02

Engineering Design File

IDAPA Preliminary Air Screening Results



431.02 06/20/2001 Rev. 09

ENGINEERING DESIGN FILE

EDF- ER-315 Rev. No. 0 Page 1 of 1

1.	Title: IDAPA	Prelimi	nary Ai	r Screening F	Result	s			
2.	Project File No	.: NA							
3.	Site Area and I	Building	No.:	NA	4.	SSC	Identification/Equip	ment Tag No.:	NA
5.	Summary: This doc evaluation of II constituents. T	cument DAPA 5 he syst	preser 8.01.0 em be cility (l	nts the calcula 1.585 and 58 ing evaluated	.01.0 inclu	for ai 1.586 des o	r compliance for no requirements was i perations and main n ponds, and Stagii	nradionuclide co made for nonrad tenance of the II	onstituents. An lionuclide NEEL
6.	Review (R) and								
	(See instruction						nce of signatures.)		Date
Dor	former	R/A	туре	ed Name/Orga Tina Rout		BOH	Signat	ure	05/14/02
1 61	Torrier			CH2M HIL			Ina M.R.	onth-	03/14/02
Che	ecker	R	(Sam	e as Indepen Reviewer		Peer		1	05/14/02
	ependent Peer viewer	Α		Marty Doorni BBWI	oos/		hart for	venlo	05/14/02
App	orover	Α		Thomas Bors BBWI	chel/		Mon 1 1	Bork	05/14/02
Re	questor	Ac		Don Verno BBWI	n/		D. Ven	^	05/14/02
7.	Distribution: (Name and Mail S	top)	M. Do	ornbos, MS 3	930;	D. Ve	rnon, MS 3930; T. I	Borschel, MS 39	30
8.	Records Mana	gemen	t Unifo	rm File Code	(UFC	;):			
	Disposition Aut	thority:					Retention Perio	d:	
	EDF pertains to	o NRC	license	ed facility or IN	VEEL	SNF	program?: 🗌 Yes	□No	
9.	Registered Pro								

ABSTRACT

This document presents the preliminary calculations for air screening of nonradionuclide constituents. An evaluation of Idaho Administrative Procedures Act 58.01.01.585 and 58.01.01.586 requirements was made for nonradionuclide constituents. The system being evaluated includes operations and maintenance of the INEEL CERCLA Disposal Facility landfill, evaporation ponds, and Staging, Storage, Sizing, and Treatment Facility.

CONTENTS

ABS	TRAC	ЭТ	iii
ACR	ONYI	MS	vii
1.	PUR	RPOSE	1-1
	1.1	Requirements	1-1
	1.2	IDAPA Evaluation	
2.	GIV	EN/ASSUMED INFORMATION	2-1
	2.1	Evaluation Outline	2-1
		2.1.1 Calculations Required for Comparison to Tabled Values	2-1 2-10
3.	CON	NCLUSIONS	3-1
4.	DEV	VELOPMENT OF OPERATIONAL LIMITS	4-1
5.	REF	ERENCES	5-1

Appendix A—SCREEN3 Model—Output File

Appendix B—Back-Calculation of Maximum Allowable Soil Concentrations and Comparison to WAC Concentrations

vi

ACRONYMS

AAC ambient air concentration

AACC annual ambient air concentration

ARARs applicable or relevant and appropriate requirements

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CFR Code of Federal Regulations

EDF engineering design file

EL emission level

EPA Environmental Protection Agency

ICDF INEEL CERCLA Disposal Facility

IDAPA Idaho Administrative Procedures Act

IDEQ Idaho Department of Environmental Quality

INEEL Idaho National Environmental Engineering Laboratory

MEI maximally exposed individual

NA not applicable

NTV no tabled value

OU operating unit

RF release factor

ROD Record of Decision

SCRAM Support Center for Regulatory Air Models

SVOC semi-volatile organic compound

SSSTF Staging, Storage, Sizing, and Treatment Facility

VOC volatile organic compound

WAC Waste Acceptance Criteria

IDAPA Preliminary Air Screening Results

1. PURPOSE

The purpose of this preliminary air screening evaluation engineering design file (EDF) is to evaluate Idaho Administrative Procedures Act (IDAPA) 58.01.01.585 and 58.01.01.586 requirements. IDAPA regulations require a direct comparison of inventory to tabled values given in IDAPA 58.01.01.585 and 58.01.01.586. If all constituents are below the tabled values, no further analysis is required. For any constituents exceeding the tabled values, IDAPA requires performance of modeling of those constituents.

Modeling used in this evaluation consists of a screening model *SCREEN3*, which is listed on the Environmental Protection Agency's (EPA's) Support Center for Regulatory Air Models (SCRAM) website (SCRAM 2000) as a screening tool that can be used preceding a refined modeling analysis (if refinement is required). This screening model is a simple, single-source Gaussian plume model that provides maximum ground-level concentrations for point, area, flare, and volume sources. The model is suitable to this air evaluation due to the fact that there is only one area source and there are no sensitive receptors (58.01.01.007.10) within 0.4 km (.25 mile) of the facility. A more detailed dispersion model (e.g., *ISC3* [SCRAM 2000]) will be prepared for determination of operational limitations for each constituent included in both the design inventory and the appropriate IDAPA 585/586 tables. This detailed model will be prepared as part of a subsequent remedial action work plan.

The system being evaluated includes operations and maintenance of the INEEL CERCLA Disposal Facility (ICDF) landfill, evaporation ponds, and activities at the Staging, Storage, Sizing, and Treatment Facility (SSSTF).

1.1 Requirements

The applicable or relevant and appropriate requirements (ARARs) identified in the Final Record of Decision (ROD) operation unit (OU) 3-13 (DOE-ID 1999) include the state requirements listed in IDAPA 58.01.01.585 and 58.01.01.586 for nonradionuclides.

1.2 IDAPA Evaluation

This evaluation included a preliminary comparison of nonradionuclides to the tabled values given in the Idaho Administrative Code, IDAPA 58.01.01.585 and 58.01.01.586. Section 223.04 Exemption Criteria and Reporting Requirements for Toxic Air Pollutant Emissions, "Level III Exemption" of this code describes the reporting requirements for toxic air pollutants. Under this requirement, no permit to construct for toxic air pollutants is required for a source that satisfies reporting limits listed in IDAPA 58.01.01.585 and 58.01.01.586. For constituents that exceeded the reporting limits, modeling using SCREEN3 was performed.

For a Level III exemption, "the source shall satisfy the following criteria:

a) The uncontrolled concentration at the point of compliance [i.e., INEEL site boundary] (Section 210), for all toxic air pollutants emitted by the source shall be less than or equal to all applicable ambient concentrations listed in Sections 585 and 586; and b) The controlled emission rate for all toxic air pollutants emitted by the source shall be less than or equal to all applicable screening emission levels listed in Sections 585 and 586."

This requirement is further described in Section 210.06 "Uncontrolled Ambient Conditions." These requirements are listed below:

- a) "Compare the source's or modification's uncontrolled ambient concentration at the point of compliance for the toxic air pollutant to the applicable acceptable ambient concentration listed in Section 585 or 586.
- b) If the source's or modification's uncontrolled ambient concentration at the point of compliance is less than or equal to the applicable acceptable ambient concentration, no further procedures for demonstrating preconstruction compliance will be required for that toxic air pollutant as part of the application process."

2. GIVEN/ASSUMED INFORMATION

The operations associated with the remediation activities that must be considered include the air screening for activities associated with the landfill, and storage, handling, and disposal of waste at the ICDF Complex. Table 2-1 lists the nonradionuclide design inventory and the tabled values from IDAPA 58.01.01.585 and 58.01.01.586. These values consist of given information in this analysis. This table also includes the comparison to IDAPA 58.01.01.585 and 58.01.01.586, which is discussed in Section 3.2.

2.1 Evaluation Outline

2.1.1 Calculations Required for Comparison to Tabled Values

The given design inventory (EDF-ER-264) for the soil was converted to an inventory in air using the following calculations:

- 1. Determine the total mass of soil from the source in a single year (i.e., the ICDF Complex). This was calculated by assuming that 36% of the total capacity of the landfill (510,000 yd³) would be used in a given year of operation (EDF-ER-290). This gives an annual volume of 183,600 yd³/yr. This volume was then multiplied by the density of the loose, moist soil (3,477 lb/yd³) in the geotechnical report (DOE-ID 2000a) to determine the total mass of soil for a single year (638 million lbm/yr) (see Table 2-1, footnote a).
- 2. Determine the annual contamination for each constituent. This was calculated by taking the total mass of soil for a single year (kg) and multiplying it by the design inventory for each constituent (mg/kg). This gives the annual contamination mass (mg), which was then converted to lb_m for comparison to the emission level (EL) values given in IDAPA 58.01.01.585 and 58.01.01.586. This mass was then divided by the total number of hours in a single year to give an emission rate for each constituent (lb_m/hr).
- 3. Determine the amount of each contamination that would be released into the air. Release factors (RF) were applied to each of the emission rates calculated in the previous step. For volatile constituents an RF of 1.0 was used, for semi-volatile constituents and miscellaneous other constituents an RF of 1E 03 and was used, and inorganic constituents an RF of 1E 06 was used. The basis for determining which constituents are volatile or semi-volatile is from DOE-ID 2000b, and laboratory testing methodologies (e.g., 8021B, 8260B, 8270C, 8275A, and 8410) (EPA 1997).
- 4. Compare the calculated emission rate to the EL values listed in IDAPA 58.01.01.585 and 58.01.01.586. The factored emission rates were then directly compared to the listed values. The results of this comparison are shown in Table 2-1 (see "Direct Comparison" column for both IDAPA 58.01.01.585 and 58.01.01.586 evaluations).
- 5. Evaluate results of comparison. For values that are below listed values, no further evaluation is required. (Note that for several constituents no tabled values are listed in the IDAPA 58.01.01.585 and 58.01.01.586 tables. No additional evaluation was performed for these constituents.) For values that are above the listed values, a screening model *SCREEN3* was used.

Results of the modeling are shown in Table 2-2. The use of this screening model for this EDF evaluation is supported by both the IDAPA requirements as well as the 40 CFR 51, Appendix W requirements.

Table 2-1. Preliminary comparison of nonradionuclide constituents to IDAPA 58.01.01.585 and 58.01.01.586 screening emission levels.

						IDAPA 58.01.01.585	585		IDAPA 58.01.01.586	36
	Design			` `	Emission	Acceptable Ambient			Acceptable Ambient	
	Inventory	Annual	Delege	Inventory	Levels	Concentrations	Direct	Emission Levels (FL)	Concentrations (AACC)	Direct
Constituent	(Soil) (mg/kg)	Contamination (1b _m)	Refease Factor ^b	(lb/hr) ^c	(Ib/hr)	(mg/m³)	Comparison ^d	- 1	(µg/m³)	Comparison ^d
1,1,1-Trichloroethane	1.57E - 02	1.00E + 01	1.00E + 00	1.14E - 03	1.27E + 02	9.55E + 01		VTV	NTV	NA
1,1,2,2-Tetrachloroethane	4.95E - 05	3.16E - 02	1.00E + 00	3.60E - 06	NTV	VTV	N A	1.10E - 05	1.70E - 02	
1,1,2-trichloroethane	2.42E - 04	1.55E - 01	1.00E + 00	1.76E - 05	NTV	VTV	NA	4.20E - 04	6.20E - 02	
1,1-Dichloroethane	2.34E - 03	1.49E + 00	1.00E + 00	1.70E - 04	2.70E + 01	2.05E + 01		2.50E - 04	3.80E - 02	
1,1-Dichloroethene	1.48E - 03	9.44E - 01	1.00E + 00	1.08E - 04	VTV	VTN	NA	2.50E - 04	3.38E+00	
1,2,4-Trichlorobenzene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	2.47E + 00	1.85E + 00		VTV	VTN	Ϋ́Z
1,2-Dichlorobenzene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	2.00E + 01	1.50E + 01		VTV	VTV	NA V
1,2-dichloroethane	5.38E - 06	3.43E - 03	1.00E + 00	3.92E - 07	2.67E + 00	2.00E + 00		2.50E - 04	3.80E - 02	
1,2-Dichloroethene (total)	3.24E - 04	2.07E - 01	1.00E + 00	2.36E - 05	5.27E + 01	3.95E + 01		2.50E - 04	3.80E - 02	
1,3-Dichlorobenzene ⁸	1.14E - 02	7.26E + 00	1.00E + 00	8.29E - 04	NTV	VTV	ZA	VTV	VTV	NA
1,4-Dichlorobenzene	4.50E - 01	2.87E + 02	1.00E - 03	3.28E - 05	3.00E + 01	2.25E + 01		VTV	VTV	NA
1,4-Dioxane	1.88E - 05	1.20E - 02	1.00E + 00	1.37E - 06	VTV	VTV	NA	4.80E - 03	7.10E - 01	
2,4,5-Trichlorophenol	4.46E - 02	2.85E + 01	1.00E - 03	3.25E - 06	NTV	1.60E - 03	NA	VTV	VTV	NA
2,4,6-Trichlorophenol	1.83E - 02	1.17E + 01	1.00E - 03	1.33E - 06	NTV	NTV	NA A	1.20E - 03	1.80E - 01	
2,4-Dichlorophenol	2.16E - 02	1.38E + 01	1.00E - 03	1.57E - 06	VTN	NTV	NA	NTV	NTV	NA
2,4-Dimethylphenol	1.83E - 02	1.17E + 01	1.00E - 03	1.33E - 06	NTV	NTV	NA	NTV	NTV	NA
2,4-Dinitrophenol	5.09E - 02	3.25E + 01	1.00E - 03	3.71E - 06	VTV	VTV	N A	NTV	NTV	Y Y
2,4-Dinitrotoluene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	NTV	NTV	NA	VTV	NTV	NA V
2,6-Dinitrotoluene	2.07E - 02	1.32E + 01	1.00E - 03	1.51E - 06	NTV	NTV	NA AN	NTV	NTV	Y Y
2-Butanone, see Methyl ethyl ketone	2.47E - 02	1.58E + 01	1.00E + 00	1.80E - 03	3.93E + 01	2.95E + 01		NTV	VTV	N A
2-Chloronaphthalene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	NTV	NTV	Y Y	VTV	NTV	Y.
2-Chlorophenol (and all isomers) (ID)	1.83E - 02	1.17E + 01	1.00E - 03	1.33E - 06	3.30E - 02	2.50E - 02		VTV	VTV	Y Z
2-Hexanone, see Methyl n-butyl ketone	2.70E - 03	1.72E + 00	1.00E + 00	1.96E - 04	1.33E+00	1.00E + 00) NTN	NT/	V Z

Table 2-1. (continued).

IDAPA 58.01.01.586

IDAPA 58.01.01.585

Direct Comparison ^d	NA	AN	NA	A'Z	NA	NA A	NA AN	NA	Y V	NA	NA A	NA A	ŊĄ	NA	NA	NA	NA	NA	NA	NA	NA		NA	NA
Acceptable Ambient Concentrations (AACC) (µg/m³)	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	VTV	NTV	NTV	VTV	VTV	VTV	VTV	VTV	VTV	VTV	1.50E - 02	VTV	NTV
Emission Levels (EL) (1b/hr)		NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	VTV	NTV	VTV	VTV	VTV	VTV	VTV	VTV	VTV	9.80E - 05	NTV	NTV
Direct Comparison ^d	NA		NA	NA	NA	NA	NA		NA A	NA	NA	NA				NA	NA	NA				NA		NA
Acceptable Ambient Concentrations (AAC) (mg/m³)	VTV	1.10E + 00	VTV	NTV	VTV	NTV	NTV	1.00E - 02	NTV	NTV	NTV	NTV	1.03E + 01	1.10E + 00	1.50E - 01	VTV	VTV	VTN .	8.90E + 01	3.35E+00	1.25E - 02	VTV	5.00E - 01	NTV
Emission Levels (EL) (lb/hr)	NTV	1.47E + 00	NTV	NTV	VTV	NTV	NTV	1.30E - 02	VTV	VTV	VTV	NTV	1.37E + 01	1.47E + 00	2.00E - 01	NTV	NTV	NTV	1.19E + 02	4.47E + 00	1.70E - 02	NTV	6.67E - 01	NTV
Inventory Air (lb/hr) ^c	3.73E - 05	1.50E - 06	1.98E - 06	1.33E - 06	8.29E - 07	1.63E - 08	1.98E - 06	3.25E - 06	8.29E - 07	1.33E - 06	2.97E - 06	8.29E - 07	2.16E - 03	2.81E - 06	1.98E - 06	3.75E - 06	1.47E - 05	1.51E - 06	4.52E - 02	1.37E - 06	6.60E - 07	6.60E - 07	5.15E - 04	2.33E - 05
Release Factor ^b	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	-1.00E + 00	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E + 00	1.00E + 00	1.00E + 00	1.00E + 00	1.00E - 06	1.00E - 03
Annual Contamination ^a (Ib _m)	3.27E + 02	1.32E + 01	1.74E + 01	1.17E + 01	7.26E + 00	1.43E - 01	1.74E + 01	2.85E + 01	7.26E + 00	1.17E + 01	2.60E + 01	7.2 6E + 00	1.89E + 01	2.46E + 01	1.74E + 01	3.29E + 01	1.29E + 02	1.32E + 01	3.96E + 02	1.20E - 02	5.78E - 03	5.78E - 03	4.52E + 06	2.04E + 02
Design Inventory (Soil) (mg/kg)	5.12E - 01	2.06E - 02	2.72E - 02	1.83E - 02	1.14E - 02	2.23E - 04	2.72E - 02	4.46E - 02	1.14E - 02	1.83E - 02	4.08E - 02	1.14E - 02	2.96E - 02	3.86E - 02	2.72E - 02	5.16E - 02	2.02E - 01	2.07E - 02	6.20E - 01	1.88E - 05	9.06E - 06	9.06E - 06	7.08E + 03	3.20E - 01
Constituent	2-Methylnaphthalene	2-Methylphenol	2-Nitroaniline	2-Nitrophenol	3,3'-Dichlorobenzidine	3-Methyl Butenyl	3-Nitroaniline	4,6-Dinitro-2-methylphenol	4-Bromophenyl-phenyl ether	4-Chloro-3-methylphenol	4-Chloroaniline	4-Chlorophenylphenylphenylether	4-Methyl-2-Pentanone	4-Methylphenol	4-Nitroaniline	4-Nitrophenol	Acenaphthene	Acenaphthylene	Acetone	Acetonitrile	Acrolein	Acrylonitrile	Aluminum	Anthracene

Table 2-1. (continued).

1.586			Comparison	NA							NA			NA	5	NA	NA	NA	NA		NA				NA
IDAPA 58.01.01.586	Acceptable Ambient	Concentrations (AACC)	(ˈmg/m՜)	NTN	1.40E - 01	1.00E - 02	1,00E - 02	1.00E - 02	1.00E - 02	2.30E - 04	VTV	1,20E - 01	1.50E - 05	NTV	3.00E - 04	NTV	VTV	NTV	VTV	4.20E - 03	NTV	3.00E - 03	5.00E - 02	4.20E + 00	VTV
		E E	(lb/hr)	NTV	9.30E - 04	6.60E - 05	6.60E - 05	6.60E - 05	6.60E - 05	1.50E - 06	NTV	8.00E - 04	9.90E - 08	VTV	2.00E-06	NTV	ALV	VTV	VTV	2.80E - 05	NTV	2.00E - 05	3.30E - 04	2.80E - 02	NTV
.585			Comparison		NA	NA	NA	NA	NA	NA		X	NA	NA	Ž	NA	NA	NA	NA	NA	NA	NA	NA	NA	
IDAPA 58.01.01.585	Acceptable Ambient	Concentrations (AAC)	(mg/m′)	2.50E - 02	NTV	NTV	NTV	VTV	VTV	NTV	2.50E - 02	AIN	NTV	VTV	MTW	VTV	VTV	VTV	NTV	VTV	NTV	VTV	NTV	VTV	5.00E - 02
	Emission	Levels (EL)	(Ib/hr)	3.30E - 02	NTV	NTV	VTV	NTV	NTV	NTV	3.30E - 02	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTN	NTV	6.70E - 02
		Inventory Air	(lb/hr)	4.25E - 07	8.34E - 09	5.60E - 07	5.60E - 07	5.60E - 07	5.60E - 07	4.12E - 07	1.31E - 05	4.39E - 02	2.12E - 08	1.84E - 05	7.64E = 06	1.31E - 05	8.29E - 07	1.35E - 06	6.23E - 07	2.09E - 08	8.29E - 07	8.29E - 07	8.29E - 07	1.07E - 05	1.34E - 05
			Factor	1.00E - 06	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 06	1.00E - 06	1.00E + 00	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 06	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 06
		Annual Contamination ^a	(Ib _m)	3.72E + 03	7.31E - 02	4.91E + 00	4.91E + 00	4.91E + 00	4.91E + 00	3.61E + 03	1.15E + 05	3.85E + 02	1.86E - 01	1.62E + 02	6.69E+01	1.15E + 02	7.26E + 00	1.19E + 01	5.46E + 00	1.83E + 02	7.26E + 00	7.26E + 00	7.26E + 00	9.39E + 01	1.18E + 05
	Design	Inventory (Soil)	(mg/kg)	5.83E + 00	1.15E - 04	7.69E - 03	7.69E - 03	7.69E - 03	7.69E - 03	5.65E+00	1.79E + 02	6.03E-01	2.91E - 04	2.53E - 01	1.05E - 01	1.79E - 01	1.14E - 02	1.86E - 02	8.56E - 03	2.87E - 01	1.14E - 02	1.14E - 02	1.14E - 02	1.47E - 01	1.85E + 02
			Constituent	Antimony & compounds, as Sb (handling & use)	Aramite	Aroclor-1016	Aroclor-1254	Aroclor-1260	Aroclor-1268	Arsenic compounds	Barium, soluble	Collipoulius, as Da Benzene	Benzidine	Benzo(a)anthracene	Benzo(a)pyrene	Benzo(b)fluoranthene	Benzo(g,h,i)perylene	Benzo(k)fluoranthene	Benzoic acid	Beryllium & compounds	bis(2- Chloroethoxy)methane	bis(2-Chloroethyl)ether	bis(2-Chloroisopropyl)ether g	bis(2-Ethylhexyl)phthalate 1.47E - 01	Boron (as anhydrous tetra 1.85E + 02 borate)

Table 2-1. (continued).

01.01.586	table ient rations Direct	ට	V NA	V NA	- 04	V NA	V NA	V NA		V NA	V NA	- 01	V NA	V	V NA	۷ NA	V	V NA	V NA	V NA		V NA	V NA	
IDAPA 58.01.01.586	Acceptable Ambient Concentrations (AACC)		NTV	VTV	5.60E - 04	NTV	VTV	NTV	VTV	NTV	VTN	2.80E - 01	VTV	NTV	VTV	VTV	VTV	VTV	VTV	VTV	VTV	VTV	VTV	
	Emission Levels (EL)	1	VTV	VTV	3.70E - 06	VTV	VTV	VTV	VTV	VTV	VTV	1.90E - 03	VTV	NTV	VTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	
.585	Direct	Comparison ^d	N A	NA	NA		NA							NA						NA	NA		NA	
IDAPA 58.01.01.585	Acceptable Ambient Concentrations	(mg/m^3)	VTN	VTV	VTV	5.00E - 02	VTV	1.50E + 00	1.50E - 01	1.75E + 01	1.32E + 02	5.15E + 00	2.50E - 02	VTV	2.50E - 03	5.00E - 02	2.50E - 01	7.50E - 02	1.20E + 01	NTV	VTV	2.50E - 01	VTV	
	Emission Levels (EL)	(lb/hr)	NTV	NTV	NTV	6.67E - 01	NTV	2.00E + 00	2.00E - 01	2.33E + 01	1.76E + 02	6.69E + 00	3.30E - 02	VTV	3.30E - 03	6.70E - 02	3.33E - 01	1.00E - 01	1.60E + 01	NTV	VTV	3.33E - 01	VTV	
	Inventory Air	(lb/hr) ^c	3.60E - 09	4.95E - 06	2.61E - 07	1.49E - 03	2.36E - 06	3.32E - 03	1.36E - 04	4.79E - 04	2.20E - 07	2.57E - 05	3.00E - 06	1.93E - 05	4.40E - 07	2.18E - 06	2.45E - 05	7.28E - 05	2.16E - 06	8.29E - 07	2.36E - 05	8.29E - 07	2.15E - 07	
	Release	1	1.00E - 03	1.00E - 03	1.00E - 06	1.00E - 06	1.00E - 03	1.00E + 00	1.00E - 03	1.00E + 00	1.00E + 00	1.00E + 00	1.00E - 06	1.00E - 03	1.00E - 06	1.00E - 06	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	1.00E - 03	
	Annual Contamination ^a	(lb _m)	3.16E - 02	4.34E + 01	2.29E + 03	1.30E + 07	2.07E + 01	2.91E + 01	1.19E + 03	4.20E + 00	1.93E - 03	2.25E - 01	2.63E + 04	1.69E + 02	3.85E + 03	1.91E + 04	2.15E + 02	6.38E + 02	1.89E + 01	7.26E + 00	2.07E + 02	7.27E + 00	1.89E + 00	
	Design Inventory (Soil)	(mg/kg)	4.95E - 05	6.79E - 02	3.59E + 00	2.04E + 04	3.23E - 02	4.55E - 02	1.87E + 00	6.57E - 03	3.02E - 06	3.53E - 04	4.12E + 01	2.65E - 01	6.04E + 00	2.99E + 01	3.37E - 01	1.00E + 00	2.96E - 02	1.14E - 02	3.24E - 01	1.14E - 02	2.96E - 03	
		Constituent	Butane, 1, 1, 3, 4- Tetrachloro-	Butylbenzylphthalate	Cadmium and compounds	Calcium (as calcium carbonate)	Carbazole	Carbon disulfide	Chloride (as chlorine)	Chlorobenzene	Chloroethane-see-Ethyl chloride	Chloromethane	Chromium (III) compounds, as Cr	Chrysene	Cobalt (metal, dust & fume)	Copper (dusts & mists)	Cyanide and compounds as CN	Cyclonite	Diacetone alcohol	Dibenz(a,h)anthracene	Dibenzofuran	Diethylphthalate	Dimethyl Disulfide	

Table 2-1. (continued).

					II	IDAPA 58.01.01.585	585	I	IDAPA 58.01.01.586	98
	Design				Emission	Acceptable Ambient			Acceptable Ambient	
	Inventory (Soil)	Annual Contamination ^a	Release	Inventory Air	Levels (EL)	Concentrations (AAC)	Direct	Emission Levels (EL)	Concentrations (AACC)	Direct
Constituent	(mg/kg)	(Ib _m)	Factor ^b	(lb/hr) ^c	(lb/hr)	(mg/m ³)	Comparison ^d	1	(µg/m³)	Comparison ^d
Di-n-butylphthalate	2.39E - 02	1.52E + 01	1.00E - 03	1.74E - 06	3.33E - 01	2.50E - 01		NTV	VTV	NA
Di-n-octylphthalate	2.62E - 02	1.67E + 01	1.00E - 03	1.91E - 06	3.33E-01	2.50E - 01		VTV	VTV	NA
Dysprosium	5.93E + 01	3.79E + 04	1.00E - 03	4.32E - 03	NTV	VTV	NA	VTV	VTV	NA
Eicosane	2.83E - 03	1.81E + 00	1.00E - 03	2.06E - 07	NTV	VTV	NA	NTV	VTV	NA
Ethyl cyanide (as cyanide)	1.88E - 05	1.20E - 02	1.00E + 00	1.37E - 06	3.33E - 01	2.50E - 01		NTV	NTV	NA
Ethylbenzene	7.81E - 02	4.98E + 01	1.00E + 00	5.69E - 03	2.90E + 01	2.18E + 01		VTV	NTV	NA
Famphur	5.81E - 05	3.71E - 02	1.00E - 03	4.23E - 09	NTV	VTV	NA	VTV	VTV	NA A
Fluoranthene	7.62E - 01	4.87E + 02	1.00E - 03	5.55E - 05	NTV	VTV	NA	NTV	NTV	NA
Fluorides, as F	3.87E + 00	2.47E + 03	1.00E - 03	2.82E - 04	1.67E - 01	1.25E - 01		NTV	NTV	N A
Heptadecane, 2,6,10,15- Tetra	3.44E - 03	2.20E + 00	1.00E - 03	2.50E - 07	NTV	VTV	Y Y	VTV	NTV	NA
Hexachlorobenzene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	NTV	VTV	NA	1.30E - 05	2.00E - 03	
Hexachlorobutadiene	2.07E - 02	1.32E + 01	1.00E - 03	1.51E - 06	NTV	VTV	NA	3.30E - 04	5.00E - 02	
Hexachloro- cyclopentadiene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	7.00E - 03	5.00E - 03		VIV	NTV	NA
Hexachloroethane	1.14E - 02	7.26E + 00	1.00E + 00	8.29E - 04	NTV	VTV	NA	1.70E - 03	2.50E - 01	
Indeno(1,2,3-cd)pyrene	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	NTV	VTV	NA	NTV	VTV	NA
Iron (iron salts, soluable, as Fe)	1.02E + 04	6.54E + 06	1.00E - 06	7.46E - 04	6.70E - 02	5.00E - 02		VTV	NTV	N A
Isobutyl alcohol	1.88E - 05	1.20E - 02	1.00E + 00	1.37E - 06	1.00E + 01	6.00E + 00		NTV	VTV	NA
Isophorone	1.14E - 02	7.27E + 00	1.00E - 03	8.29E - 07	1.87E + 04	1.40E + 00		VTV	VTV	NA
Isopropyl Alcohol/2-propanol	6.20E - 01	3.96E + 02	1.00E + 00	4.52E - 02	6.53E + 01	4.90E + 01		VTV	NTV	NA
Kepone	9.92E - 02	6.33E + 01	1.00E - 03	7.22E - 06	NTV	VTV	NA	VTV	VTV	NA
Lead	5.76E + 01	3.68E + 04	1.00E - 06	4.19E - 06	NTV	VTV	NA	NTV	NTV	NA
Magnesium (magnesium oxide fume)	4.47E + 03	2.86E + 06	1.00E - 06	3.26E - 04	6.67E - 01	5.00E - 01		NTV	NTV	NA

Table 2-1. (continued).

				,		IDAPA 58.01.01.585	585		IDAPA 58.01.01.586	98
Design Inventory (Soil) (mg/kg)	gn Cory I) cg)	Annual Contamination ^a (lb _m)	Release Factor ^b	Inventory Air (1b/hr) [¢]	Emission Levels (EL) (lb/hr)	Acceptable Ambient Concentrations (AAC) (mg/m³)	Direct Comparison ^d	Emission Levels (EL) (lb/hr)	Acceptable Ambient Concentrations (AACC) (µg/m³)	Direct Comparison ^d
2.07E + 02	+ 02	1.32E + 05	1.00E - 06	1.51E - 05	3.33E - 01	2.50E - 01		NTV	NTV	NA
9.45E+00	00+	6.03E + 03	1.00E - 06	6.88E - 07	7.00E - 03	5.00E - 03		NTV	NTV	NA
2.96E - 02	3 - 02	1.89E + 01	1.00E - 03	2.16E - 06	4.00E + 00	3.00E + 00		NTV	NTV	NA
4.841	4.84E - 04	3.09E - 01	1.00E + 00	3.53E - 05	4.07E + 01	3.05E + 01		NTN	NTV	NA
1.02E	1.02E + 01	6.50E + 03	1.00E - 06		3.33E - 01	2.50E - 01		VTV	NTV	NA
4.25	4.25E - 01	2.71E + 02	1.00E - 03	3.10E - 05	3.33E + 00	2.50E + 00		NTV	NTV	NA
1.97	1.97E + 01	1.25E + 04	1.00E - 06	1.43E - 06	NTV	NTV	NA	2.70E - 05	4.20E - 03	
3.93	3.93E+00	2.51E + 03	1.00E - 03	2.86E - 04	3.33E - 01	2.50E - 01		NTV	NTV	NA
2.23	2.22E - 01	1.42E + 02	1.00E - 03	1.62E - 05	3.33E - 01	2.50E - 01		NTV	VTV	NA
8.4	8.49E - 03	5.42E + 00	1.00E - 03	6.18E - 07	3.33E - 01	2.50E - 01		NTV	VTV	NA
1.14	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	3.33E - 01	2.50E - 01		VTV	VTV	NA
1.1	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	VTV	NTV	NA	NTV	VTV	NA
1.1	1.14E - 02	7.26E + 00	1.00E - 03	8.29E - 07	NTV	NTV	NA	VTV	NTV	NA
1.6	1.61E - 04	1.03E - 01	1.00E - 03	1.18E - 08	9.33E + 01	7.00E + 01		VTV	NTV	NA
5.00	5.06E - 03	3.23E + 00	1.00E - 03	3.68E - 07	NTV	NTV	NA	VTV	NTV	NA
5.59	5.59E - 02	3.57E + 01	1.00E - 03	4.07E - 06	3.30E - 02	2.50E - 02		NTV	NTV	NA
1.17	1.17E+00	7.46E + 02	1.00E - 03	8.51E - 05	NTV	NTV	NA	VTV	VTV	NA
7.98	7.98E - 02	5.09E + 01	1.00E - 03	5.81E - 06	1.27E + 00	9.50E - 01		NTV	VTV	NA
1.83	1.83E - 02	1.17E + 01	1.00E - 03	1.33E - 06	NTV	NTV	NA	NTV	NTV	NA
9.74	9.74E + 01	6.22E + 04	1.00E - 06	7.09E - 06	7.00E - 03	5.00E - 03		NTV	VTV	NA
1.13	1.13E + 03	7.20E + 05	1.00E - 06	8.21E - 05	1.33E - 01	1.00E - 01		NTV	NTV	NA

Table 2-1. (continued).

				•	П	IDAPA 58.01.01.585	585	I	IDAPA 58.01.01.586	98
	Design				Emission	Acceptable Ambient			Acceptable Ambient	
	Inventory (Soil)	Annual Contamination ^a	Release	Inventory Air	Levels (EL)	Concentrations (AAC)	Direct	Emission Levels (EL.)	Concentrations (AACC)	Direct
Constituent	(mg/kg)	- 1	Factorb	(lb/hr) ^c	(lb/hr)	(mg/m³)	Comparison ^d	(1b/hr)	$(\mu g/m^3)$	Comparison ^d
p-Toluenesulfonamide	5.06E - 03	3.23E + 00	1.00E - 03	3.68E-07	VTV	VTV	NA	NTV	NTV	NA
Pyrene	2.53E - 01	1.62E + 02	1.00E - 03	1.84E - 05	NTV	VTV	NA	NTV	NTV	NA
Selenium	8.46E - 01	5.40E + 02	1.00E - 06	6.16E - 08	1.30E - 02	1.00E - 02		NTV	NTV	NA
Silver Soluble compounds, as Ag	9.84E + 00	6.28E + 03	1.00E - 06	7.16E - 07	1.00E - 03	5.00E - 03		NTV	VTN	NA
Sodium (as sodium hydroxide)	2.11E + 02	1.35E + 05	1.00E - 06	1.54E - 05	1.33E - 01	1.00E - 01		NTV	VTN	NA
Strontium	1.82E + 01	1.16E + 04	1.00E - 03	1.33E - 03	NTV	VTV	NA	NTV	NTV	NA
Styrene (styrene monomer)	1.03E - 06	6.55E - 04	1.00E + 00	7.47E - 08	6.67E + 00	1.00E + 00		VTV	NTV	NA
Sulfate (as sulfuric acid)	2.05E + 01	1.31E + 04	1.00E - 03	1.50E - 03	6.70E - 02	5.00E - 02		NTV	NTV	N A
Sulfide (as sulfuric acid)	7.59E + 02	4.84E + 05	1.00E - 03	5.52E - 02	6.70E - 02	5.00E - 02		NTV	NTV	NA
Terbium	5.73E + 02	3.66E + 05	1.00E - 03	4.17E - 02	NTV	VTV	NA	NTV	NTV	NA
Tetrachloroethene (as tetrachloroethylene)	9.64E - 03	6.15E + 00	1.00E + 00	7.02E - 04	NTV	VTV	NA	1.30E - 02	2.00E + 00	
Thallium, soluble Compounds, as T1	3.70E - 01	2.36E + 02	1.00E - 06	2.70E - 08	7.00E - 03	5.00E - 03		VTV	NTV	NA
Toluene (toluol)	9.82E - 01	6.27E + 02	1.00E + 00	7.15E - 02	2.50E + 01	1.88E + 01		NTV	NTV	NA
Tributylphosphate	3.64E - 01	2.32E + 02	1.00E - 03	2.65E - 05	1.47E - 01	1.10E - 01		VTV	NTV	NA
Trichloroethene (as trichloroethylene)	7.20E - 02	4.60E + 01	1.00E + 00	5.25E - 03	1.79E + 01	1.35E + 01		NTV	NTV	N A
Trinitrotoluene	1.00E + 00	6.38E + 02	1.00E - 03	7.28E - 05	NTV	VTV	NA	VTV	NTV	N A
Undecane, 4, 6-Dimethyl-	1.61E - 04	1.03E - 01	1.00E - 03	1.18E - 08	NTV	VTV	NA	VTV	NTV	NA
Vanadium, as V205 Respirable Dust & fume	2.12E + 01	1.36E + 04	1.00E - 06	1.55E - 06	3.00E - 03	2.50E - 03		VTV	NTV	Y Y
Xylene (o-, m-,p-isomers)	3.45E+00	2.21E + 03	1.00E + 00	2.52E - 01	2.90E + 01	2.18E + 01		VTV	VTV	NA
Ytterbium	1.95E + 02	1.25E + 05	1.00E - 03	1.42E - 02	6.70E - 02	5.00E - 02		VTV	NTV	NA
Zinc metal (ID)	2.08E + 02	1.33E + 05	1.00E - 06	1.51E - 05	6.67E - 01	5.00E - 01		VTV	NTV	NA

Table 2-1. (continued)

				•	Π	IDAPA 58.01.01.585	585	I	IDAPA 58.01.01.586	98
	Design				Emission	Acceptable Ambient			Acceptable Ambient	
	Inventory	Annual		Inventory	Levels	ŭ		Emission	Concentrations	
	(Soil) C	Contamination ^a	Release		(EL)	(AAC)		\vdash	(AACC)	Direct
Constituent	(mg/kg)	(lb _m)	Factorb	(lb/hr) ^c	(lb/hr)	(mg/m³)	Comparison ^d	(lb/hr)	(µg/m³)	Comparison ^d
Zirconium compounds as $6.91E + 01$ $4.41E + 04$	6.91E + 01	4.41E + 04	1.00E - 06	0E-06 5.03E-06 3.33E-01	3.33E - 01	2.50E - 01		NTV	NTV	NA

NA = Not applicable. No tabled value listed for comparison. NTV = No tabled value given in IDAPA 58.01.01.585 and 58.01.01.586.

Total mass of material to be disposed at ICDF in a given year is calculated using the following equation:

Total Mass = Total Volume of ICDF and Pond for a single year x density of soil

yd³/yr	lb/yd³	lb_m/yr	kg/yr
183,600	3,477	6.38E + 08	2.90E + 08
36% Total Design Volume: (Total volume 510,000 yd ³ * 36%)	Density of Soile:	Total mass/year:	Total mass/year:

The total mass (kg) is multiplied by the soil inventory (mg/kg) to determine mass of each constituent in the soil (mg). This mass is then converted to pounds for comparison with tabled values.

- An RF is used to determine the amount of a constituent that is reasonably expected to become airborne. Since VOCs have a potential for 100% release, an RF of 1.0 was used. However, there is currently no regulatory guidance for determination of RFs for chemical constituents; therefore, an RF of 1.0E - 03 has been assumed for all SVOC constituents and 1.0E - 6 for all inorganic constituents (e.g., metals), since it is reasonable to assume significantly less of these constituents could potentially become airborne.
- Annual contamination (Ibm) is divided by 8,766 hours/year to obtain a comparable value to IDAPA 58.01.01.585 and 58.01.01.586 EL values.
- This is a direct comparison of the Design Inventory in Air to the EL values listed in IDAPA 58.01.01.585 and 58.01.01.586. For constituents that indicate "HIGH", further analysis is required. Results of this further analysis are shown in Table 2-2. For cells that are blank or indicate "NA" the evaluation is complete.
- The density shown is a wet density using a dry density of 3,280.5 lb/yd3 and a moisture content of 6% (DOE-ID 2000a).
- Classification of constituents into VOC, SVOC, etc. for determination of RF are based in part on DOE-ID 2000b. For constituents not listed there, laboratory testing methods 8021B, 8260B, 8270C, 8275A, and 8410 (EPA 1997) were used to classify constituents.
- These constituents are listed as both a VOC and SVOC in laboratory sampling methodologies. The RF values for VOCs have been used for added conservatism.

2.1.2 Calculations Required for Modeling using SCREEN3

The SCREEN3 model calculates ground-level concentrations at specified distances, including the INEEL site boundary, which is the point of compliance. Inputs to this model include the source type (e.g., area, point, flair), emission rate (g/s-m²), source height, length, and width of the source, height of the receptor, and location of source (e.g., urban or rural). Input values used are as follows:

- 1. Source type: area
- 2. Emission rate: This was calculated using the following equation: Emission rate $(g/s-m^2) = (Volume of soil/year \times density of soil / seconds per year) / area of source. [(510,000 yd³ * 36%) × (3,477 lb/yd³) × (454 g/lb) / <math>3.16 \times 10^7$ sec/yr)] / 129,600 m² = 0.0708 g/s-m²
- 3. Source height: 1 m
- 4. Length and width of source (estimated based on total area of ICDF and evaporation pond): 360 m x 360 m
- 5. Receptor height: 2 m
- 6. Location of source: Rural.

Results of the model gave a calculated concentration at specific distances from the source. The output of the SCREEN3 model is included in Appendix A. The value at the closest INEEL site boundary (11,418 m) was used for the remaining evaluation. The concentration at the boundary calculated by SCREEN3 (1.85E + 05 μ g/m³) was multiplied by the original soil inventory for each modeled constituent. Per IDAPA 58.01.01, a persistence factor of 0.125 was then applied. This value was then compared directly to the acceptable ambient concentrations (mg/m³) listed in IDAPA 58.01.01.585 and 58.01.01.586. These results are shown in Table 2-2. The model showed that benzene and methylene chloride are below annual acceptable ambient concentrations (AACC), but that benzo(a)pyrene exceeds the AACC.

Table 2-2. Comparison of modeling results with constituents exceeding IDAPA 58.01.01.585 and 58.01.01.586 acceptable ambient concentrations.

Constituent	Design Inventory (Soil) (mg/kg)	IDAPA 585 (24-Hour) Acceptable Ambient Concentrations (AAC) (mg/m³)	IDAPA 586 (Annual) Acceptable Ambient Concentrations (AACC) (µg/m³)	SCREEN3 [™] Modeled Concentration (µg/m³) ^a	Comparison of Modeling Results IDAPA 585	-
Benzene	6.03E - 01	NTV	1.20E - 01	1.40E - 02	NA	OK
Benzo(a)pyrene	1.05E - 01	NTV	3.00E - 04	2.42E - 03	NA	Operationally Limited
Methylene Chloride	8.36E - 02	NTV	2.40E - 01	1.93E - 03	NA	OK

NA = Not applicable. No tabled value listed for comparison.

NTV = No tabled value given in IDAPA 58.01.01.585.

a. This value was determined by multiplying the SCREEN3 modeled concentration at the closest boundary by the design inventory for each constituent and multiplied by a persistence factor per IDAPA 58.01.01 (e.g., for benzene $1.85E + 05 \mu g/m^3 \times 6.03E - 01 mg/kg \times 1.0E - 06 kg/mg \times 0.125 = 1.40E - 05 \mu g/m^3$).

3. CONCLUSIONS

The preliminary evaluation (comparison to IDAPA 58.01.01.585 and 58.01.01.586 tabled values) determined that three constituents exceeded the tabled values. Each of these constituents was then modeled using *SCREEN3*. The model showed that all constituents are below the acceptable ambient concentrations listed in IDAPA 58.01.01.585 and 58.01.01.586, except for benzo(a)pyrene. Development of operational limits will be performed as part of the remedial action work plan, as described in Section 4.

4. DEVELOPMENT OF OPERATIONAL LIMITS

The modeling performed for this EDF was to show that the landfill's design inventory is in compliance with IDAPA 585/586 tabled values. As a precursor to the operational modeling activities, a comparison of "maximum allowable" concentrations to the waste acceptance criteria (WAC) (DOE-ID 2002) concentrations was performed and is included in Appendix B.

This "back-calculation" is to determine the maximum allowable soil concentrations (mg/kg) that will meet the IDAPA 585/586 tabled emission levels (lb/hr). It is based on similar parameters used in development of Table 2-1 (e.g., same soil mass, density); however, for this calculation it has been assumed that all materials will be released (i.e., RF = 1). Also included in this calculation is a list of the WAC values and a comparison of these WAC values to the maximum allowable soil concentrations. Instances when the WAC values exceed the calculated maximum concentrations have also been identified. The following equation (1) was used to develop the maximum allowable concentrations.

$$Max_{Allowable} \frac{mg}{kg} = \frac{\left(fEL\frac{lb}{hr}x365\frac{days}{year}x24\frac{hours}{day}\right)}{RFx2.2E - 06\frac{lb}{mg}xMASS\frac{kg}{year}}$$
(1)

where,

 $Max_{Allowable} = Operational Limit (mg/kg)$

f = factor applied to IDAPA 585/586 tables for iterative approach

EL = IDAPA 585/586 emission levels (lb/hr)

RF = 1.0

MASS = total mass of soil evaluated is based on 36% of the total capacity of landfill.

A more refined modeling effort will be performed as part of the remedial action work plan in order to develop operational limits for the ICDF and associated facilities. The EPA approved models proposed for this evaluation include an emissions model, WATER9, and a dispersion model, ISC3.

• Emission modeling:

SSSTF and ICDF Landfill: The WATER9 is proposed for modeling emissions of the ICDF. This model estimates VOC emissions from treatment, storage, and disposal facility processes. The emissions model is described in the EPA Handbook for Air Toxics Emission Inventory Development: Volume I: Stationary Sources (EPA 1998) and Air Emissions Models for Waste and Wastewater (EPA 1994). The model includes calculations of emissions from disposal impoundments, closed landfills, land treatment facilities, and aeration and nonaeration impoundment processes. Input parameters include landfill design and operation parameters, waste physical characteristics, and hazardous waste chemical properties. Advantages are that the model was designed for landfill operations of hazardous wastes and estimates emissions based on compound specific chemical properties, etc. (potentially most accurate).

Disadvantages are that the model can be complex to run if a large number of compounds have been identified and the amount of input parameters is potentially significant (as well as the amount of assumptions).

<u>Evaporation Pond</u>: For the evaporation pond, the proposed emission model is *WATER9*. This program is an analytical model for estimating compound-specific air emissions from wastewater collection and treatment systems. The emissions model is described in the EPA document Air Emissions Models for Waste and Wastewater (EPA 1994).

• Dispersion modeling:

It is proposed that the final modeling analysis for primary toxic air pollutants of concern (e.g., for those constituents that exceed ELs and/or AAC/AACCs) will be performed using a refined dispersion model. *ISC3* is the proposed preferred refined model. Data inputs include a meteorological package (developed from site-specific data), coordinates for receptor locations (coordinates), source locations (coordinates), elevations, emission rates and parameters, hours of operation, building dimensions, terrain descriptions, sensitive receptors/receptor locations, co-contributing sources, etc., meeting EPA and Idaho Department of Environmental Quality (IDEQ) guidelines.

A modeling protocol identifying the proposed modeling procedures will be prepared in accordance to IDEQ guidelines and then submitted for approval prior to use.

5. REFERENCES

- 40 CFR 51, Code of Federal Regulations, "Appendix W, To Part 51—Guideline On Air Quality Models", Washington, D.C.
- DOE-ID, 2002, Waste Acceptance Criteria for ICDF Landfill, DOE/ID-10865, Rev. 2, U.S. Department of Energy Idaho Operations Office, Idaho Falls, Idaho, May 2002.
- DOE-ID, 2000a, Geotechnical Report for the Conceptual Design of the INEEL CERCLA Disposal Facility at Waste Area Group 3, Operable Unit 3-13, DOE/ID-10812, Rev. 0, U.S. Department of Energy Idaho Operations Office, Idaho Falls, Idaho.
- DOE-ID, 2000b, Quality Assurance Project Plan for Waste Area Groups 1, 2, 3, 4, 5, 6, 7, 10, and Inactive Sites, DOE/ID-10587, Rev. 6, U.S. Department of Energy Idaho Operations Office, Idaho Falls, Idaho.
- DOE-ID, 1999, Final Record of Decision, Idaho Nuclear Technology and Engineering Center, Operable Unit 3-13, DOE/ID-10660, Rev. 0, Department of Energy Idaho Operations Office, Idaho Falls, Idaho, U.S. Environmental Protection Agency Region 10, and State of Idaho Department of Health and Welfare.
- EDF-ER-264, 2001, "INEEL CERCLA Disposal Facility Design Inventory," Rev. A, Environmental Restoration Program, Idaho National Engineering and Environmental Laboratory, March 2001.
- EDF-ER-290, 2002, "NESHAP Modeling for ICDF Complex," Rev. 1, Environmental Restoration Program, Idaho National Engineering and Environmental Laboratory, May 2002.
- EPA, 1998, Handbook for Air Toxics Emission Inventory Development: Volume I: Stationary Sources EPA-454/B-98-002, U.S. Environmental Protection Agency.
- EPA, 1997, Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846, 3rd Edition, as amended by Updates I (July, 1992), IIA (August, 1993), IIB (January, 1995), and III, U.S. Environmental Protection Agency, Washington, D.C.
- EPA, 1994, Air Emissions Models for Waste and Wastewater, EPA-453/R-94-080A, U.S. Environmental Protection Agency.
- IDAPA 58.01.01, 1994, "Rules for the Control of Air Pollution in Idaho," Idaho Administrative Procedures Act, Idaho Department of Environmental Quality (as promulgated May 1, 1994).
- SCRAM, 2002, Support Center for Regulatory Air Models (SCRAM), SCREEN3, ISC3, http://www.epa.gov/ttn/scram/, U.S. Environmental Protection Agency.

THE CONTENTS OF THIS SECTION ARE THE HIGHEST QUALITY AVAILABLE

INITIAL 9 DATE 9/21/02

PAGE NUMBERING SEQUENCE IS INCONSISTENT

Appendix A SCREEN3 Model—Output File

```
03/19/02
11:20:10
*** SCREEN3 MODEL RUN ***
*** VERSION DATED 96043 ***
CID 023 - EDF-315 IDAPA COMPLIANCE
SIMPLE TERRAIN INPUTS:
 SOURCE TYPE
            = AREA
 EMISSION RATE (G/(S-M**2)) = .708000E-01
 SOURCE HEIGHT (M) =
                        1.0000
 LENGTH OF LARGER SIDE (M) = 360.0000
 LENGTH OF SMALLER SIDE (M) = 360.0000
                         2.0000
 RECEPTOR HEIGHT (M) =
 URBAN/RURAL OPTION
                        RURAL
THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED.
THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.
 MODEL ESTIMATES DIRECTION TO MAX CONCENTRATION
BUOY. FLUX = .000 \text{ M}**4/\text{S}**3; MOM. FLUX = .000 \text{ M}**4/\text{S}**2.
*** FULL METEOROLOGY ***
 *********
 *** SCREEN DISCRETE DISTANCES ***
 *********
** TERRAIN HEIGHT OF 0. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES **
 DIST CONC
               U10M USTK MIX HT PLUME MAX DIR
 (M) (UG/M**3) STAB (M/S) (M/S) (M) HT (M) (DEG)
 100.
       .4338E+07 6 1.0 1.0 10000.0 1.00 45.
 500.
      .3317E+07 6 1.0 1.0 10000.0 1.00 45.
 1000. .1849E+07 6 1.0 1.0 10000.0 1.00 45.
                                        44.
 5000.
       .4716E+06 6 1.0 1.0 10000.0 1.00
11418. .1846E+06 6 1.0 1.0 10000.0 1.00 45.
20000. .9455E+05 6 1.0 1.0 10000.0 1.00
        .5861E+05 6 1.0 1.0 10000.0 1.00
30000.
                                          37.
40000. .4229E+05 6 1.0 1.0 10000.0 1.00
                                          31.
50000. .3283E+05 6 1.0 1.0 10000.0 1.00
                                         42.
 60000.
        .1334E+05 6 2.0 2.0 10000.0 1.00
                                          31.
  ************
  *** SUMMARY OF SCREEN MODEL RESULTS ***
  **********
CALCULATION MAX CONC DIST TO TERRAIN
 PROCEDURE (UG/M**3) MAX (M) HT (M)
 ----- ----<del>---</del>
 SIMPLE TERRAIN .4338E+07 100.
                                 0.
 ************
** REMEMBER TO INCLUDE BACKGROUND CONCENTRATIONS **
```

THE CONTENTS OF THIS SECTION ARE THE HIGHEST QUALITY AVAILABLE

INITIAL 9 DATE 9/21/02

PAGE NUMBERING SEQUENCE IS INCONSISTENT

Appendix B

Back-Calculation of Maximum Allowable Soil Concentrations and Comparison to WAC Concentrations

Table B-1. Back calculation of maximum allowable soil concentration for comparison to WAC concentrations.

Maximum Soil able	= Operationally	Comparison of WAC to Max Value (DAPA 586)	NA	Operationally limited	Operationally limited	Operationally limited	Operationally limited	NA	NA	Operationally limited	Operationally limited	NA	NA	OK	NA
Comparison of WAC Values to Maximum Soil Concentration Allowable	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	Comparison of WAC to Max Value (DAPA 585)	OK	NA A	NA	OK	NA	OK	OK	OK	OK	NA	Operationally limited	NA	NA
Comparison o	(If WAC > All	WAC Concentration (10865 App D) (mg/kg)	1.6E + 01	5.0E - 02	2.4E - 01	2.3E + 00	1.5E + 00	1.1E + 01	1.1E + 01	5.4E - 03	3.2E - 01	1.1E + 01	4.4E + 01	1.9E - 02	4.5E + 01
of Allowable Soil	DAPA 585 and 586 Levels [lb/hr])	Maximum Allowable Soil Inventory for 586 Comparison (mg/kg)	VTV	1.51E - 04	5.77E - 03	3.44E - 03	3.44E - 03	NTV	NTV	3.44E - 03	3.44E - 03	VTV	VTV	6.60E - 02	NTV
Back Calculation of Allowable Soil	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	Maximum Allowable Soil Inventory for 585 Comparison (mg/kg)	1.75E + 03	VTV	VTN	3.71E + 02	VTV	3.40E + 01	2.75E + 02	3.67E + 01	7.25E + 02	NTV	4.12E + 02	NTV	VTN
	IDAPA 58.01.01.586	Emission Levels (EL) (lb/hr)	NTV	1.10E - 05	4.20E - 04	2.50E - 04	2.50E - 04	NTV	NTV	2.50E - 04	2.50E - 04	NTV	VTV	4.80E - 03	NTV
	IDAPA IDAPA 58.01.01.585 58.01.01.586	Emission Levels (EL)	1.27E + 02	VTV	VTV	2.70E + 01	NTV	2.47E + 00	2.00E + 01	2.67E + 00	5.27E + 01	NTV	3.00E + 01	NTV	NTV
		Constituent	1,1,1-Trichloroethane	1,1,2,2-Tetrachloroethane	1,1,2-trichloroethane	H 1,1-Dichloroethane	1,1-Dichloroethene	1,2,4-Trichlorobenzene	1,2-Dichlorobenzene	1,2-dichloroethane	1,2-Dichloroethene (total)	1,3-Dichlorobenzene ^g	1,4-Dichlorobenzene	1,4-Dioxane	2,4,5-Trichlorophenol

_	
7	7
70	į
Ξ	=
3	
Cont	
5	
۶	
۲	-
_	
α	
Ω	
D O	
D of	
 Pable D	

Maximum Soil ble	= Operationally	Comparison of WAC to Max Value (DAPA 586)	Operationally limited	NA	NA AN	NA AN	N.A.	NA AN	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Comparison of WAC Values to Maximum Soil Concentration Allowable	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	Comparison of WAC to Max Value (DAPA 585)	NA	NA	NA	NA	NA	NA	ОК	NA	Operationally limited	OK	NA	Operationally limited	NA	NA	NA	NA
Comparison o	(If WAC > All	WAC Concentration (10865 App D) (mg/kg)	1.8E + 01	2.2E + 01	1.8E + 01	5.1E + 01	1.1E + 01	2.1E + 01	2.5E + 01	1.1E + 01	1.8E + 01	2.7E + 00	5.1E + 02	2.1E + 01	1.0E - 01	1.8E + 01	1.1E + 01	3.3E + 04
of Allowable Soil	IDAPA 585 and 586 Levels [lb/hr])	Maximum Allowable Soil Inventory for 586 Comparison (mg/kg)	1.65E - 02	VTV	VTV	NTV	VTV	VTV	NTV	NTV	VTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV
Back Calculation of Allowable Soil	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	Maximum Allowable Soil Inventory for 585 Comparison (mg/kg)	NTV	NTV	VTV	VTV	NTV	NTV	5.40E + 02	VTV	4.54E - 01	1.83E + 01	NTV	2.02E + 01	VTV	VTV	NTV	NTV
	IDAPA 58.01.01.586	Emission Levels (EL) (lb/hr)	1.20E - 03	NTV	NTV	NTV	NTV	NTV	NTV	NTV	NTV	VTV	VTV	NTV	NTV	NTV	VTV	VTV
	IDAPA IDAPA 58.01.01.585 58.01.01.586	Emission Levels (EL) (lb/hr)	NTV	NTV	VTV	NTV	NTV	VTV	3.93E + 01	VTV	3.30E - 02	1.33E + 00	NTV	1.47E + 00	NTV	NTV	NTV	NTV
		Constituent	2,4,6-Trichlorophenol	2,4-Dichlorophenol	2,4-Dimethylphenol	2,4-Dinitrophenol	2,4-Dinitrotoluene	2,6-Dinitrotoluene	2-Butanone, see Methyl ethyl ketone	2-Chloronaphthalene	2-Chlorophenol (and all isomers) (ID)	2-Hexanone, see Methyl nbutyl ketone	2-Methylnaphthalene	2-Methylphenol	2-Nitroaniline	2-Nitrophenol	3,3'-Dichlorobenzidine	3-Methyl Butenyl

Table B-1. (continued).	•						
			Downship of Allowable Soil	of Allowable Soil	Comparison o	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil Ible
	DAPA DAPA 58.01.01.585	IDAPA 58.01.01.586	Inventory (Based on IDAPA 585 and Tabled Emission Levels [lb/hr])	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	(If WAC > All	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally
•		,	Maximum Allowable Soil	Maximum Allowable Soil Inventory for 586	WAC	Comparison of WAC to Max	Comparison of WAC to Max
Constituent	Levels (EL) (1b/hr)	Levels (EL) (lb/hr)	Comparison (mg/kg)	Comparison (mg/kg)	(10865 App D) (mg/kg)	Value (DAPA 585)	Value (IDAPA 586)
3-Nitroaniline	NTV	NTV	VTV	NTV	1.0E - 01	NA	NA
4,6-Dinitro-2-methylphenol	1.30E - 02	VTV	1.79E - 01	VTV	4.5E + 01	Operationally limited	NA
4-Bromophenyl-phenyl ether	VTV	VTN	NTV	VIN	8.5E + 04	NA	NA
4-Chloro-3-methylphenol	NTV	NTV	NTV	NTV	9.6E + 04	NA	NA
4-Chloroaniline	VTV	NTV	NTV	NTV	4.1E + 01	NA	NA
4-Chlorophenyl-phenylether	NTV	NTV	NTV	NTV	1.0E + 05	NA	NA
4-Methyl-2-Pentanone	1.37E + 01	NTV	1.88E + 02	NTV	3.0E + 01	OK	NA
4-Methylphenol	1.47E + 00	NTV	2.02E + 01	NTV	3.9E + 01	Operationally limited	NA
4-Nitroaniline	2.00E - 01	VTV	2.75E + 00	NTV	1.0E - 01	OK	NA
4-Nitrophenol	NTV	NTV	NTV	VTV	5.2E + 01	NA	NA A
Acenaphthene	VTV	VTV	VTV	NTV	2.0E + 02	N.A.	NA
Acenaphthylene	VTV	VTV	NTV	VTV	2.1E + 01	NA	NA
Acetone	1.19E + 02	VTV	1.64E + 03	VTV	9.9E + 01	OK	NA
Acetonitrile	4.47E + 00	VTV	6.15E + 01	VTV	1.2E + 00	OK	NA
Acrolein	1.70E - 02	NTV	2.34E - 01	NTV	5.5E - 01	Operationally limited	NA
Acrylonitrile	NTV	9.80E - 05	NTV	1.35E - 03	5.8E - 01	NA	Operationally

Table B-1. (continued).							
			Back Calculation of Allowable Soil	of Allowable Soil	Comparison of	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil able
	IDAPA IDAPA 58.01.01.585 58.01.01.5	IDAPA 58.01.01.586	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	IDAPA 585 and 586 Levels [lb/hr])	(If WAC > Allo	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally ()
-			Maximum Allowable Soil	Maximum Allowable Soil	WAC	Comparison of	Comparison of
	Emission Levels (EL)	Emission Levels (EL)	Inventory for 585 Comparison	Inventory for 586 Comparison	Concentration (10865 App D)	WAC to Max Value	WAC to Max Value
Constituent	(lb/hr)	(lb/hr)	(mg/kg)	(mg/kg)	(mg/kg)	(IDAPA 585)	(IDAFA 380) limited
Aluminum	6.67E - 01	NTV	9.17E + 00	NTV	1.6E + 05	Operationally limited	NA A
Anthracene	VTV	NTV	NTV	NTV	3.2E + 02	NA	NA
Antimony & compounds, as Sb (handling & use)	3.30E - 02	VTV	4.54E - 01	VTV	5.8E + 03	Operationally limited	NA
Aramite	NTV	9.30E - 04	VTV	1.28E - 02	6.7E + 00	NA	Operationally limited
Aroclor-1016	VTV	6.60E - 05	VTV	9.07E - 04	7.7E + 00	NA	Operationally limited
Aroclor-1254	VTV	6.60E - 05	VTV	9.07E - 04	1.3E + 02	NA	Operationally limited
Aroclor-1260	VTV	6.60E - 05	VTV	9.07E - 04	5.0E + 02	NA	Operationally limited
Aroclor-1268	NTV	6.60E - 05	VTV	9.07E - 04	6.2E + 01	NA	Operationally limited
Arsenic compounds	NTV	1.50E - 06	VTN	2.06E - 05	5.8E + 01	NA	Operationally limited
Barium, soluble compounds, as Ba	3.30E - 02	VTV	4.54E - 01	NTV	3.0E + 03	Operationally limited	NA
Benzene	NTV	8.00E - 04	VTV	1.10E - 02	2.2E + 02	NA	Operationally limited

_	
π	
đ	
=	
\$	
ç	
- 0	1
hamina	
`	
_	
- 1	ł
ď	
oble	
_	
2,	
Ç	C
r	

			-		Comparison o	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil able
8	IDAPA 8.01.01.585	IDAPA IDAPA 58.01.01.585 58.01.01.586	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	DAPA 585 and 586 Levels [lb/hr])	(If WAC > All	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally
Constituent	Emission Levels (EL) (lb/hr)	Emission Levels (EL) (lb/hr)	Maximum Allowable Soil Inventory for 585 Comparison (mg/kg)	Maximum Allowable Soil Inventory for 586 Comparison (mg/kg)	WAC Concentration (10865 App D) (mg/kg)	Comparison of WAC to Max Value (DAPA 585)	Comparison of WAC to Max Value (DAPA 586)
Benzidine	NTV	9.90E - 08	NTV	1.36E - 06	1.7E + 01	NA	Operationally limited
Benzo(a)anthracene	NTV	NTV	NTV	NTV	2.5E + 02	NA	A N
Benzo(a)pyrene	NTV	2.00E - 06	NTV	2.75E - 05	1.1E + 02	NA	Operationally limited
Benzo(b)fluoranthene	NTV	VTV	NTV	NTV	1.8E + 02	NA	NA
Benzo(g,h,i)perylene	NTV	NTV	NTV	NTV	1.1E + 01	NA	NA
Benzo(k)fluoranthene	NTV	VTV	NTV	NTV	1.9E + 01	NA	NA
Benzoic acid	NTV	NTV	NTV	NTV	8.6E+00	NA	NA
Beryllium & compounds	NTV	2.80E - 05	NTV	3.85E - 04	1.8E + 01	NA	Operationally limited
bis(2-Chloroethoxy)methane	NTV	NTV	NTV	NTV	1.6E + 02	NA	NA
bis(2-Chloroethyl)ether	VTV	2.00E - 05	NTV	2.75E - 04	1.1E + 01	NA	Operationally limited
$_{g}^{b}$ is (2-Chloroisopropyl) ether	NTV	3.30E - 04	NTV	4.54E - 03	1.1E + 01	NA	Operationally limited
bis(2-Ethylhexyl)phthalate	VTV	2.80E - 02	NTV	3.85E - 01	1.5E + 02	NA	Operationally limited
Boron (as anhydrous tetra borate)	6.70E - 02	NTV	9.21E - 01	NTV	3.3E + 03	Operationally limited	NA
Butane, 1, 1, 3, 4-Tetrachloro-	NTV	NTV	VTV	NTV	1.0E + 05	NA	NA
Butylbenzylphthalate	NTV	NTV	NTV	VTV	6.8E + 01	NA	NA

(continued)
7
Q.
-
- }-
-:-
Ċ
- 7
_
٠,
_
R.1
α
_
đ
ahle
_
τ``

Aaximum Soil ble	- Operationally		Comparison of WAC to Max	Value (DAPA 586)	Operationally limited	NA	NA	NA	NA	NA	NA	Operationally limited	NA	NA	NA	NA	NA
Comparison of WAC Values to Maximum Soil Concentration Allowable	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)		Comparison of WAC to Max	Value (DAPA 585)	NA	NA	NA	Operationally limited	Operationally limited	OK	OK	OK	Operationally limited	NA	Operationally limited	Operationally limited	Operationally limited
Comparison o	(If WAC > All		WAC Concentration	(10865 App D) (mg/kg)	3.6E + 03	No Limit	3.2E + 01	4.6E + 01	3.3E + 04	6.6E + 00	1.5E - 01	3.5E - 01	4.1E + 04	2.7E + 02	1.1E + 02	3.0E + 04	3.4E + 02
of Allowable Soil	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	Maximum	Allowable Soil Inventory for 586	Comparison (mg/kg)	5.09E - 05	NTV	VTV	VTV	NTV	NTV	VTV	2.61E - 02	NTV	NTV	NTV	NTV	NTV
Back Calculation of Allowable Soil	Inventory (Based on IDAPA 585 and Tabled Emission Levels [lb/hr])	Maximum	Allowable Soil Inventory for 585	Comparison (mg/kg)	NTV	9.17E + 00	VTV	2.75E + 01	2.75E + 00	3.20E + 02	2.42E + 03	9.19E + 01	4.54E - 01	NTV	4.54E - 02	9.21E - 01	4.58E + 00
	DAPA 58.01.01.586		Emission	Levels (EL) (lb/hr)	3.70E - 06	NTV	NTV	VTV	NTV	NTV	NTV	1.90E - 03	NTV	NTV	VTN	VTV	NTV
	DAPA DAPA 58.01.01.585 58.01.01.586		Emission	Levels (EL) (lb/hr)	NTV	6.67E - 01	NTV	2.00E + 00	2.00E - 01	2.33E + 01	1.76E + 02	6.69E + 00	3.30E - 02	NTV	3.30E - 03	6.70E - 02	3.33E - 01
	·			Constituent	Cadmium and compounds	Calcium (as calcium carbonate)	Carbazole	Carbon disulfide	Chloride (as chlorine)	Chlorobenzene	Chloroethane-see-Ethyl chloride	Chloromethane	Chromium (III) compounds, as Cr	Chrysene	Cobalt (metal, dust & fume)	Copper (dusts & mists)	Cyanide and compounds as CN

_
-
1
ч
2
-
=
=
_
_
_

	DAPA DAPA	DAPA 58 01 01 586	Back Calculation of Allowable Soil Inventory (Based on IDAPA 585 and 5	Back Calculation of Allowable Soil Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels (Ib/hrd)	Comparison o Coi (If WAC > All.	Comparison of WAC Values to Maximum Soil Concentration Allowable (If WAC > Allowable Soil Conc = Operationally Limited (FYCERD)	Maximum Soil lble
			Maximum	Maximum			
	Emission Levels (EL)	Emission Levels (EL)	Allowable 5011 Inventory for 585 Comparison	Allowable Soll Inventory for 586 Comparison	WAC Concentration (10865 App D)	Comparison of WAC to Max	Comparison or WAC to Max Value
Constituent	(Ib/hr)	(lb/hr)	(mg/kg)	(mg/kg)	(mg/kg)	(IDAPA 585)	(IDAPA 586)
Cyclonite	1.00E - 01	NTV	1.37E + 00	NTV	No Limit	NA	NA
Diacetone alcohol	1.60E + 01	VTV	2.20E + 02	NTV	1.0E + 05	Operationally limited	NA
Dibenz(a,h)anthracene	NTV	NTV	NTV	NTV	1.1E + 01	NA	NA
Dibenzofuran	NTV	NTV	NTV	NTV	3.2E + 02	NA	NA
Diethylphthalate	3.33E - 01	NTV	4.58E + 00	NTV	1.1E + 01	Operationally limited	NA
Dimethyl Disulfide	VTV	NTV	VTV	NTV	3.3E + 04	NA	NA
Dimethylphthalate	3.33E - 01	NTV	4.58E + 00	NTV	1.1E + 01	Operationally limited	NA
Di-n-butylphthalate	3.33E - 01	NTV	4.58E + 00	NTV	2.4E + 01	Operationally limited	NA
Di-n-octylphthalate	3.33E - 01	NTV	4.58E + 00	NTV	2.6E + 01	Operationally limited	NA
Dysprosium	NTV	NTV	NTV	NTV	5.9E + 04	NA	NA
Eicosane	NTV	NTV	NTV	VIV	1.0E + 05	NA	NA
Ethyl cyanide (as cyanide)	3.33E - 01	NTV	4.58E + 00	NTV	3.3E + 04	Operationally limited	NA
Ethylbenzene	2.90E + 01	NTV	3.99E + 02	VTV	7.8E + 01	OK	NA
Famphur	VTN	NTV	NTV	NTV	1.0E + 05	NA	NA
Fluoranthene	NTV	NTV	NTV	NTV	7.6E + 02	NA	NA

Hexachlorobenzene	NTV	1.30E - 05	VTN	1.79E - 04	1.1E + 01	NA	Operationally
							limited
Hexachlorobutadiene	NTV	3.30E - 04	NTV	4.54E - 03	2.1E+01	NA	Operationally limited
Hexachlorocyclopentadiene	7.00E - 03	NTV	9.62E - 02	NTV	1.1E + 01	Operationally limited	NA
Hexachloroethane	VTV	1.70E - 03	NTV	2.34E - 02	1.1E + 01	NA	Operationally limited
Indeno(1,2,3-cd)pyrene	NTV	NTV	VTV	NTV	1.1E + 01	NA	NA
Iron (iron salts, soluable, as Fe)	6.70E - 02	NTV	9.21E - 01	NTV	2.4E + 05	Operationally limited	NA
Isobutyl alcohol	1.00E + 01	NTV	1.37E + 02	NTV	1.2E + 00	OK	NA
Isophorone	1.87E + 04	NTV	2.57E + 05	VTV	1.1E + 01	OK	NA
Isopropyl Alcohol/2- propanol	6.53E + 01	NTV	8.98E + 02	NTV	1.0E + 05	Operationally limited	NA
Kepone	NTV	NTV	NTV	NTV	9.9E + 01	NA	NA
Lead	NTV	NTV	NTV	VTV	5.8E + 04	NA	NA
Magnesium (magnesium	6.67E - 01	NTV	9.17E + 00	VTV	1.2E + 05	Operationally	NA

	_	•
-	_	
•	τ	2
	Continuo	
	=	•
	Ξ	
	÷	•
•	Ξ	3
	7	-
	•	
	ζ	
	٤	
٠,		
	-	
		,
•	-	
	Υ	ı
1	Υ	
•	_	
	9	1
,	_	:
- 1	C	
•	-	
,	٠,	٠

Maximum Soil able	= Operationally	Comparison of WAC to Max	value (IDAPA 586)		NA	NA	NA	NA	Operationally limited	NA	NA	Operationally limited	NA	NA	NA
Comparison of WAC Values to Maximum Soil Concentration Allowable	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	Comparison of WAC to Max	v alue (IDAPA 585)	limited	Operationally limited	Operationally limited	Operationally limited	OK	NA	Operationally limited	Operationally limited	NA	Operationally limited	Operationally limited	Operationally limited
Comparison o	(If WAC > All	WAC Concentration	(10803 App D) (mg/kg)		4.9E + 03	9.5E + 03	1.0E + 05	4.8E - 01	2.7E+01	1.0E + 04	4.3E + 02	3.5E + 02	3.9E + 03	3.3E + 04	8.5E+00
of Allowable Soil	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [lb/hr])	Maximum Allowable Soil Inventory for 586	Comparison (mg/kg)		NTV	VTV	NTV	VTV	2.20E - 02	NTV	NTV	3.71E - 04	NTV	VTV	NTV
Back Calculation of Allowable Soil	Inventory (Based on IDAPA 585 and Tabled Emission Levels [lb/hr])	Maximum Allowable Soil Inventory for 585	Comparison (mg/kg)		4.58E + 00	9.62E - 02	5.50E + 01	5.60E + 02	NTV	4.58E + 00	4.58E + 01	NTV	4.58E + 00	4.58E + 00	4.58E + 00
	IDAPA 58.01.01.586	Emission	Leveis (EL) (lb/hr)		VTV	NTV	NTV	VTN	1.60E - 03	NTV	NTV	2.70E - 05	NTV	NTV	NTV
	IDAPA 58.01.01.585	Emission	Levels (EL) (lb/hr)		3.33E - 01	7.00E - 03	4.00E + 00	4.07E + 01	VTV	3.33E - 01	3.33E + 00	VTV	3.33E - 01	3.33E - 01	3.33E - 01
	·		Constituent	oxide fume)	Manganese as Mn (dust and compounds)	Mercury (inorganic)	Mesityl oxide	Methyl acetate	Methylene Chloride	Molybdenum as Mo Soluble compounds	Naphthalene	Nickel	Nitrate (as nitric acid)	Nitrate/Nitrite-N (as nitric acid)	Nitrite (as nitric acid)

,	_	•
٠	7	
	(parturated)	
	7	-
	Ξ	
	2	
٠	Ę	_
	٠	
	ς	
	r	٠
	7	١
	`	•
	_	_
,		
,		
,		
,	Y	
í	Y	
,	Y	
,	Y	
,		

			Back Calculation of Allowable Soil	of Allowable Soil	Comparison o	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil able
	DAPA 58.01.01.585	DAPA DAPA 58.01.01.585 58.01.01.586	Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [1b/hr])	IDAPA 585 and 586 Levels [lb/hr])	(If WAC > All	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally ()
	Emission Levels (EL)	Emission Levels (EL)	Maximum Allowable Soil Inventory for 585 Comparison	Maximum Allowable Soil Inventory for 586 Comparison	WAC Concentration (10865 App D)	Comparison of WAC to Max Value	Comparison of WAC to Max Value
Constituent	(lb/hr)	(lb/hr)	(mg/kg)	(mg/kg)	(mg/kg)	(IDAPA 585)	(IDAPA 586)
Nitrobenzene	3.33E - 01	VTV	4.58E + 00	VTN	1.1E + 01	Operationally limited	NA
N-Nitroso-di-n-propylamine	VTV	NTV	VTN	NTV	1.1E+01	NA	NA
N-Nitrosodiphenylamine	NTV	VTV	VTN	NTV	1.1E+01	NA	NA
Octane, 2, 3, 7-Trimethyl	9.33E + 01	VTV	1.28E + 03	VTN	3.3E + 04	Operationally limited	NA
o-Toluenesulfonamide	NTV	NTV	NTV	NTV	3.3E + 04	NA	NA
Pentachlorophenol	3.30E - 02	NTV	4.54E - 01	NTV	5.6E + 01	Operationally limited	NA
Phenanthrene	NTV	NTV	VTV	VTV	1.2E + 03	NA	NA
Phenol	1.27E + 00	NTV	1.75E + 01	NTV	8.0E + 01	Operationally limited	NA
Phenol, 2, 6-Bis (1, 1-Dimethyl)	NTV	NTV	NTV	NTV	1.0E + 05	NA	NA
Phosphorus	7.00E - 03	NTV	9.62E - 02	VTV	No Limit	NA	NA
Potassium (as potassium hydroxide)	1.33E - 01	NTV	1.83E + 00	VTV	4.3E + 04	Operationally limited	NA
p-Toluenesulfonamide	NTV	NTV	VTV	VTV	3.3E + 04	NA	NA
Pyrene	NTV	NTV	NTV	VTV	2.5E + 02	NA	NA
Selenium	1.30E - 02	NTV	1.79E - 01	NTV	8.5E + 02	Operationally limited	NA

Table B-1. (continued).							
				:	Comparison of Con	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil able
	IDAPA 58.01.01.585	IDAPA 58.01.01.586	Back Calculation of Allowable Soil Inventory (Based on IDAPA 585 and 586 Tabled Emission Levels [Ib/hr])	of Allowable Soil IDAPA 585 and 586 Levels [lb/hr])	(If WAC > All	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally
, trout the same of the same o	Emission Levels (EL)	Emission Levels (EL)	Maximum Allowable Soil Inventory for 585 Comparison (mo/kg)	Maximum Allowable Soil Inventory for 586 Comparison (mg/kg)	WAC Concentration (10865 App D) (mg/kg)	Comparison of WAC to Max Value (DAPA 585)	Comparison of WAC to Max Value (DAPA 586)
Silver Soluble compounds,	1.00E - 03	NTV	1.37E - 02	NTV	9.8E + 03	Operationally limited	NA
as reg Sodium (as sodium hydroxide)	1.33E - 01	VTV	1.83E + 00	NTV	3.2E + 03	Operationally limited	NA
Strontium	NTV	NTV	NTV	NTV	1.8E + 04	NA	NA
Styrene (styrene monomer)	6.67E + 00	NTV	9.17E + 01	VTV	6.1E - 02	OK	NA
Sulfate (as sulfuric acid)	6.70E - 02	NTV	9.21E - 01	VTV	3.3E + 04	Operationally limited	NA
Sulfide (as sulfuric acid)	6.70E - 02	NTV	9.21E - 01	NTV	3.3E + 04	Operationally limited	NA
Terbium	NTV	VTV	NTV	NTV	No Limit	NA	NA
Tetrachloroethene (as	NTV	1.30E - 02	NTV	1.79E - 01	9.6E + 00	NA	Operationally limited
Thallium, soluble	7.00E - 03	NTV	9.62E - 02	NTV	4.3E + 00	Operationally limited	NA A
Toluene (toluol)	2.50E + 01	NTV	3.44E + 02	NTN	3.0E + 01	Operationally limited	N'A
Tributylphosphate	1.47E - 01	VTV	2.02E + 00	VTN	4.8E + 02	Operationally limited	NA
Trichloroethene (as	1.79E + 01	VTN	2.46E + 02	VTV	3.1E + 01	OK	NA
Trinitrotoluene	NTV	NTV	NTV	NTV	1.1E + 01	NA	NA

_	٠
4	4
à	ŭ
7110	ĭ
\$	=
-:	3
۶	
9	S
6	,
_	_
_	-
-	-
D 1	1-1-0
1 0	
Johlo D 1	

			Dock Colombition of Allowable Soil	of Allowable Soil	Comparison of	Comparison of WAC Values to Maximum Soil Concentration Allowable	Maximum Soil ble
	IDAPA 58.01.01.585	DAPA DAPA 58.01.01.586	Inventory (Based on IDAPA 585 and Tabled Emission Levels [lb/hr])	Inventory (Based on DAPA 585 and 586 Tabled Emission Levels [lb/hr])	(If WAC > Allo	(If WAC > Allowable Soil Conc = Operationally Limited (EXCEED)	= Operationally
			Maximum Allowable Soil	Maximum Allowable Soil	WAC	Comparison of	Comparison of
	Emission Levels (EL)	Emission Levels (EL)	Inventory for 585 Comparison	Inventory for 586 Comparison	Concentration (10865 App D)	WAC to Max Value (TDAPA 585)	WAC to Max Value (IDAPA 586)
Undecane 4.6-Dimethyl-	NTV	NTV	NTV	VIV	3.3E + 02	NA	NA
Vanadium, as V205 Respirable Dust & fume	3.00E - 03	NTV	4.12E - 02	VTV	4.5E + 02	Operationally limited	NA
Xylene (o-, m-,p-isomers)	2.90E + 01	NTV	3.99E + 02	NTV	2.8E + 02	Operationally limited	NA
Ytterbium	6.70E - 02	NTV	9.21E - 01	NTV	No Limit	NA	NA
Zinc metal (ID)	6.67E - 01	NTV	9.17E + 00	VTN	2.1E + 05	Operationally limited	NA
Zirconium compounds as Zr 3.33E - 01	3.33E - 01 -	VTV	4.58E + 00	NTV	No Limit	NA	NA

NA = Not applicable. No tabled value listed for comparison. NTV = No tabled value given in IDAPA 585/586.